

## ZTACSR Conductor, 730.5mm<sup>2</sup>



## Specificații

Număr Fire Stal	45
Număr Fire Oțel	7
Diametru Fir Stal	4.4 mm
Diametru Fir Oțel	2.9 mm
Suprafață Secțională Fire Stal	684.2 mm <sup>2</sup>
Suprafață Secțională Fire Oțel	46.2 mm <sup>2</sup>
Suprafață Secțională Conductor	730.5 mm <sup>2</sup>
Diametru Conductor	35.1 mm
Greutate Stal	1890.7 kg/km
Greutate Oțel	361.3 kg/km
Greutate Conductor	2252.0 kg/km
Rezistență Nominală HS	N/A kN
Rezistență Nominală EHS	N/A kN
Rezistență Nominală	168.0 kN
Rezistență Nominală UHS	180.5 kN
Rezistență DC @ 20°C	0.043 Ω/km
Capacitate Curent @ 85°C	907 A
Capacitate Curent @ 150°C	1651 A
Capacitate Curent @ 210°C	2069 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.