

ACSS/TW Conductor, 565.65mm², Suwannee



Specificații

Nume Conductor	Suwannee/ACSS/TW
Suprafață Secțională Fire Aluminiu	486.26 mm ²
Suprafață Secțională Fire Oțel	79.39 mm ²
Suprafață Secțională Conductor	565.65 mm ²
Nr. Fire Aluminiu	22
Nr. Fire Oțel	2
Diametru Fir Aluminiu	7 mm
Diametru Fir Oțel	3.80 mm
Diametru Conductor	28.14 mm
Greutate Aluminiu	1343.80 kg/km
Greutate Oțel	620.11 kg/km
Greutate Conductor	1963.91 kg/km
Rezistență Nominală	137.56 kN
Rezistență Nominală HS	148.68 kN
Rezistență Nominală EHS	kN
Rezistență Nominală UHS	172.89 kN
Rezistență DC @ 20°C	0.05640 Ω/km
Capacitate Curent @ 85°C	772 A
Capacitate Curent @ 200°C	1657 A
Capacitate Curent @ 250°C	1890 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.