

ACSS/TW Conductor, 782.41mm², St. Croix



Specificații

Nume Conductor	St. Croix/ACSS/TW
Suprafață Secțională Fire Aluminiu	743.80 mm ²
Suprafață Secțională Fire Oțel	38.61 mm ²
Suprafață Secțională Conductor	782.41 mm ²
Nr. Fire Aluminiu	33
Nr. Fire Oțel	3
Diametru Fir Aluminiu	7 mm
Diametru Fir Oțel	2.65 mm
Diametru Conductor	32.82 mm
Greutate Aluminiu	2058.10 kg/km
Greutate Oțel	301.57 kg/km
Greutate Conductor	2359.67 kg/km
Rezistență Nominală	97.28 kN
Rezistență Nominală HS	104.23 kN
Rezistență Nominală EHS	kN
Rezistență Nominală UHS	116.20 kN
Rezistență DC @ 20°C	0.03740 Ω/km
Capacitate Curent @ 85°C	956 A
Capacitate Curent @ 200°C	2098 A
Capacitate Curent @ 250°C	2401 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.