

ACSS/TW Conductor, 681.37mm², Nelson



Specificații

Nume Conductor	Nelson/ACSS/TW
Suprafață Secțională Fire Aluminiu	637.03 mm ²
Suprafață Secțională Fire Oțel	44.34 mm ²
Suprafață Secțională Conductor	681.37 mm ²
Nr. Fire Aluminiu	35
Nr. Fire Oțel	3
Diametru Fir Aluminiu	7 mm
Diametru Fir Oțel	2.84 mm
Diametru Conductor	30.81 mm
Greutate Aluminiu	1764.50 kg/km
Greutate Oțel	346.37 kg/km
Greutate Conductor	2110.87 kg/km
Rezistență Nominală	99.22 kN
Rezistență Nominală HS	107.20 kN
Rezistență Nominală EHS	kN
Rezistență Nominală UHS	120.94 kN
Rezistență DC @ 20°C	0.04360 Ω/km
Capacitate Curent @ 85°C	878 A
Capacitate Curent @ 200°C	1909 A
Capacitate Curent @ 250°C	2181 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.