

KTACSR/TW Conductor, 216.97mm²



Specificații

Suprafață Secțională Fire Ktal	336.85 mm ²
Suprafață Secțională Fire Oțel	54.90 mm ²
Suprafață Secțională Conductor	391.75 mm ²
Nr. Fire Ktal	20
Nr. Fire Straturi Ktal	2
Nr. Fire Oțel	7
Diametru Fir Oțel	3.16 mm
Diametru Conductor	22.94 mm
Greutate Ktal	928.73 kg/km
Greutate Oțel	428.95 kg/km
Greutate Conductor	1357.7 kg/km
Rezistență Nominală	140.50 kN
Rezistență Nominală HS	148.18 kN
Rezistență Nominală EHS	153.67 kN
Rezistență Nominală UHS	155.59 kN
Rezistență DC @ 20°C	0.095 Ω/km
Capacitate Curent @ 85°C	579 A
Capacitate Curent @ 150°C	1017 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.