

KTACSR/TW Conductor, 681.00mm²



Specificații

Suprafață Secțională Fire Ktal	636.97 mm ²
Suprafață Secțională Fire Oțel	44.03 mm ²
Suprafață Secțională Conductor	681.00 mm ²
Nr. Fire Ktal	35
Nr. Fire Straturi Ktal	3
Nr. Fire Oțel	7
Diametru Fir Oțel	2.83 mm
Diametru Conductor	30.30 mm
Greutate Ktal	1764.8 kg/km
Greutate Oțel	344.04 kg/km
Greutate Conductor	2108.8 kg/km
Rezistență Nominală	193.31 kN
Rezistență Nominală HS	199.03 kN
Rezistență Nominală EHS	203.66 kN
Rezistență Nominală UHS	205.20 kN
Rezistență DC @ 20°C	0.050 Ω/km
Capacitate Curent @ 85°C	816 A
Capacitate Curent @ 150°C	1462 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.