

KTACSR/TW Conductor, 952.78mm²



Specificații

Suprafață Secțională Fire Ktal	891.08 mm ²
Suprafață Secțională Fire Oțel	61.70 mm ²
Suprafață Secțională Conductor	952.78 mm ²
Nr. Fire Ktal	42
Nr. Fire Straturi Ktal	3
Nr. Fire Oțel	7
Diametru Fir Oțel	3.35 mm
Diametru Conductor	35.86 mm
Greutate Ktal	2468.8 kg/km
Greutate Oțel	482.08 kg/km
Greutate Conductor	2950.9 kg/km
Rezistență Nominală	268.09 kN
Rezistență Nominală HS	276.73 kN
Rezistență Nominală EHS	282.90 kN
Rezistență Nominală UHS	285.06 kN
Rezistență DC @ 20°C	0.0361 Ω/km
Capacitate Curent @ 85°C	991 A
Capacitate Curent @ 150°C	1808 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.