


AACSR IEC 61089 -Type A2/S1B Conductor, 179.50mm² + 41.89mm²



Specificații

| | |
|-----------------------------|------------------------|
| Nume Conductor | N/A |
| Aria Secționă Conductor | N/A mm ² |
| Aria Secționă Aliaj | 179.50 mm ² |
| Aria Secționă Fire Oțel | 41.89 mm ² |
| Aria Secționă Conductor | N/A mm ² |
| Număr Fire Aluminiu | 30 |
| Număr Fire Oțel | 7 |
| Diametru Fir Aluminiu | 2.76 mm |
| Diametru Fir Oțel | 2.76 mm |
| Diametru Conductor | 19.130 mm |
| Greutate Aliaj | 496.11 kg/km |
| Greutate Oțel | 327.2 kg/km |
| Greutate Conductor | 823.3 kg/km |
| Rezistență Nominală | N/A kN |
| Clasa A Rezistență Nominală | 111.10 kN |
| Clasa B Rezistență Nominală | 109.2 kN |
| Rezistență DC @ 20°C | 0.1880 Ω/km |
| Capacitate Curent @75°C | 321 A |
| Capacitate Curent @85°C | 397 A |

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.