

AACSR IEC 61089 -Type A3/S1B Conductor, 1352mm²



Specificații

Nume Conductor	N/A
Aria Secțională Conductor	1352 mm ²
Aria Secțională Aliaj	1250 mm ²
Aria Secțională Fire Oțel	N/A mm ²
Aria Secțională Conductor	102 mm ²
Număr Fire Aluminiu	84
Număr Fire Oțel	19
Diametru Fir Aluminiu	4.103 mm
Diametru Fir Oțel	2.61 mm
Diametru Conductor	47.88 mm
Greutate Aliaj	N/A kg/km
Greutate Oțel	N/A kg/km
Greutate Conductor	4255.03 kg/km
Rezistență Nominală	490.03 kN
Clasa A Rezistență Nominală	N/A kN
Clasa B Rezistență Nominală	N/A kN
Rezistență DC @ 20°C	0.0271 Ω/km
Capacitate Curent @75°C	913 A
Capacitate Curent @85°C	1221 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.