

ACSS/TW Conductor, 908.11mm², Falcon



Specificații

Nume Conductor	Falcon/ACSS/TW
Suprafață Secțională Fire Aluminiu	805.68 mm ²
Suprafață Secțională Fire Oțel	102.43 mm ²
Suprafață Secțională Conductor	908.11 mm ²
Nr. Fire Aluminiu	42
Nr. Fire Oțel	3
Diametru Fir Aluminiu	19 mm
Diametru Fir Oțel	2.62 mm
Diametru Conductor	35.76 mm
Greutate Aluminiu	2236.70 kg/km
Greutate Oțel	801.72 kg/km
Greutate Conductor	3038.42 kg/km
Rezistență Nominală	190.84 kN
Rezistență Nominală HS	209.28 kN
Rezistență Nominală EHS	kN
Rezistență Nominală UHS	241.03 kN
Rezistență DC @ 20°C	0.03440 Ω/km
Capacitate Curent @ 85°C	1015 A
Capacitate Curent @ 200°C	2250 A
Capacitate Curent @ 250°C	2578 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.