

ACSS/TW Conductor, 794.99mm², Bluebird



Specificații

Nume Conductor	Bluebird/ACSS/TW
Suprafață Secțională Fire Aluminiu	705.42 mm ²
Suprafață Secțională Fire Oțel	89.57 mm ²
Suprafață Secțională Conductor	794.99 mm ²
Nr. Fire Aluminiu	64
Nr. Fire Oțel	4
Diametru Fir Aluminiu	19 mm
Diametru Fir Oțel	2.45 mm
Diametru Conductor	40.84 mm
Greutate Aluminiu	3046.30 kg/km
Greutate Oțel	701.06 kg/km
Greutate Conductor	3747.36 kg/km
Rezistență Nominală	166.93 kN
Rezistență Nominală HS	183.05 kN
Rezistență Nominală EHS	kN
Rezistență Nominală UHS	210.82 kN
Rezistență DC @ 20°C	0.25590 Ω/km
Capacitate Curent @ 85°C	391 A
Capacitate Curent @ 200°C	878 A
Capacitate Curent @ 250°C	1007 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.