

## KTACSR/AW Conductor, 153.72mm<sup>2</sup>



### Specificații

Număr Fire Ktal	30
Număr Fire Oțel	7
Diametru Fir Ktal	2.30 mm
Diametru Fir Oțel	2.30 mm
Suprafață Secționată Fire Ktal	124.64 mm <sup>2</sup>
Suprafață Secționată Fire Oțel	29.08 mm <sup>2</sup>
Suprafață Secționată Conductor	153.72 mm <sup>2</sup>
Diametru Conductor	16.10 mm
Greutate Ktal	343.77 kg/km
Greutate Oțel	192.47 kg/km
Greutate Conductor	536.24 kg/km
Rezistență Nominală HS	64.93 kN
Rezistență Nominală EHS	69.58 kN
Rezistență DC @ 20°C	0.2363 Ω/km
Capacitate Curent @ 85°C	341.17 A
Capacitate Curent @ 150°C	582.97 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.