


TACSR/AW Conductor, 100.88mm²



Specificații

Număr Fire Tal	15
Număr Fire Oțel	4
Diametru Fir Tal	2.60 mm
Diametru Fir Oțel	2.60 mm
Suprafață Secționată Fire Tal	79.64 mm ²
Suprafață Secționată Fire Oțel	21.24 mm ²
Suprafață Secționată Conductor	100.88 mm ²
Diametru Conductor	13.00 mm
Greutate Tal	219.14 kg/km
Greutate Oțel	142.49 kg/km
Greutate Conductor	361.63 kg/km
Rezistență Nominală HS	38.95 kN
Rezistență Nominală EHS	42.35 kN
Rezistență Nominală	N/A kN
Rezistență Nominală UHS	N/A kN
Rezistență DC @ 20°C	0.3369 Ω/km
Capacitate Curent @ 85°C	252 A
Capacitate Curent @ 150°C	422 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.