


TACSR/AW Conductor, 125.50mm²



Specificații

Număr Fire Tal	15
Număr Fire Oțel	4
Diametru Fir Tal	2.90 mm
Diametru Fir Oțel	2.90 mm
Suprafață Secționată Fire Tal	99.08 mm ²
Suprafață Secționată Fire Oțel	26.42 mm ²
Suprafață Secționată Conductor	125.50 mm ²
Diametru Conductor	14.50 mm
Greutate Tal	272.63 kg/km
Greutate Oțel	177.24 kg/km
Greutate Conductor	449.87 kg/km
Rezistență Nominală HS	48.15 kN
Rezistență Nominală EHS	52.38 kN
Rezistență Nominală	N/A kN
Rezistență Nominală UHS	N/A kN
Rezistență DC @ 20°C	0.2708 Ω/km
Capacitate Curent @ 85°C	288 A
Capacitate Curent @ 150°C	485 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.