

ZTACSR Conductor, 111.3mm²



Specificații

Număr Fire Stal	6
Număr Fire Oțel	1
Diametru Fir Stal	4.5 mm
Diametru Fir Oțel	4.5 mm
Suprafață Secționată Fire Stal	95.4 mm ²
Suprafață Secționată Fire Oțel	15.9 mm ²
Suprafață Secționată Conductor	111.3 mm ²
Diametru Conductor	13.5 mm
Greutate Stal	261.9 kg/km
Greutate Oțel	123.7 kg/km
Greutate Conductor	385.6 kg/km
Rezistență Nominală HS	N/A kN
Rezistență Nominală EHS	N/A kN
Rezistență Nominală	33.8 kN
Rezistență Nominală UHS	38.7 kN
Rezistență DC @ 20°C	0.306 Ω/km
Capacitate Curent @ 85°C	267 A
Capacitate Curent @ 150°C	448 A
Capacitate Curent @ 210°C	548 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.