

## ZTACSR Conductor, 125.5mm<sup>2</sup>



## Specificații

Număr Fire Stal	15
Număr Fire Oțel	4
Diametru Fir Stal	2.9 mm
Diametru Fir Oțel	2.9 mm
Suprafață Secționată Fire Stal	99.1 mm <sup>2</sup>
Suprafață Secționată Fire Oțel	26.4 mm <sup>2</sup>
Suprafață Secționată Conductor	125.5 mm <sup>2</sup>
Diametru Conductor	14.5 mm
Greutate Stal	272.6 kg/km
Greutate Oțel	209.3 kg/km
Greutate Conductor	481.9 kg/km
Rezistență Nominală HS	N/A kN
Rezistență Nominală EHS	N/A kN
Rezistență Nominală	50.3 kN
Rezistență Nominală UHS	57.4 kN
Rezistență DC @ 20°C	0.295 Ω/km
Capacitate Curent @ 85°C	276 A
Capacitate Curent @ 150°C	465 A
Capacitate Curent @ 210°C	569 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.