

## ZTACSR Conductor, 1167.1mm<sup>2</sup>



The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.

## Specificații

Număr Fire Stal	72
Număr Fire Oțel	19
Diametru Fir Stal	4.5 mm
Diametru Fir Oțel	1.8 mm
Suprafață Secțională Fire Stal	1119.8 mm <sup>2</sup>
Suprafață Secțională Fire Oțel	47.3 mm <sup>2</sup>
Suprafață Secțională Conductor	1167.1 mm <sup>2</sup>
Diametru Conductor	44.5 mm
Greutate Stal	3097.1 kg/km
Greutate Oțel	370.7 kg/km
Greutate Conductor	3467.7 kg/km
Rezistență Nominală HS	N/A kN
Rezistență Nominală EHS	N/A kN
Rezistență Nominală	240.0 kN
Rezistență Nominală UHS	252.8 kN
Rezistență DC @ 20°C	0.026 Ω/km
Capacitate Curent @ 85°C	1207 A
Capacitate Curent @ 150°C	2267 A
Capacitate Curent @ 210°C	2869 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.