


ACSS Conductor, 403mm², Cuckoo



Specificații

Nume Conductor	Cuckoo/ACSS
Aria sectiunii transversale	403 mm ²
Nr. fire aluminiu	24
Nr. fire otel	7
Diametru fir aluminiu	4.62 mm
Diametru fir otel	3.08 mm
Diametru Conductor	27.74 mm
Greutate Aluminiu	1114.3 kg/km
Greutate Otel	407.4 kg/km
Greutate Conductor	1521.7 kg/km
Rezistenta Nominala	96.7 kN
Rezistenta Nominala HS	104.0 kN
Rezistenta Nominala EHS	115.0 kN
Rezistenta Nominala UHS	120.2 kN
Rezistenta CC @ 20°C	0.069 Ω/km
Capacitate Curent @ 85°C	699 A
Capacitate curent @ 150°C	1496 A
Capacitate Curent @ 210°C	1706 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.