


ACSS Conductor, 456mm², Canary



Specificații

Nume Conductor	Canary/ACSS
Aria sectiunii transversale	456 mm ²
Nr. fire aluminiu	54
Nr. fire otel	7
Diametru fir aluminiu	3.28 mm
Diametru fir otel	3.28 mm
Diametru Conductor	29.51 mm
Greutate Aluminiu	1261.5 kg/km
Greutate Otel	462.0 kg/km
Greutate Conductor	1723.5 kg/km
Rezistenta Nominala	109.7 kN
Rezistenta Nominala HS	118.0 kN
Rezistenta Nominala EHS	130.4 kN
Rezistenta Nominala UHS	136.3 kN
Rezistenta CC @ 20°C	0.060 Ω/km
Capacitate Curent @ 85°C	743 A
Capacitate curent @ 150°C	1604 A
Capacitate Curent @ 210°C	1830 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.