


ACSS Conductor, 483mm², Rail



Specificații

Nume Conductor	Rail/ACSS
Aria sectiunii transversale	483 mm ²
Nr. fire aluminiu	45
Nr. fire otel	7
Diametru fir aluminiu	3.70 mm
Diametru fir otel	2.47 mm
Diametru Conductor	29.59 mm
Greutate Aluminiu	1337.1 kg/km
Greutate Otel	262.0 kg/km
Greutate Conductor	1599.1 kg/km
Rezistenta Nominala	75.2 kN
Rezistenta Nominala HS	81.2 kN
Rezistenta Nominala EHS	87.9 kN
Rezistenta Nominala UHS	91.6 kN
Rezistenta CC @ 20°C	0.057 Ω/km
Capacitate Curent @ 85°C	762 A
Capacitate curent @ 150°C	1645 A
Capacitate Curent @ 210°C	1878 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.