


ACSS Conductor, 524mm², Ortolan



Specificații

Nume Conductor	Ortolan/ACSS
Aria sectiunii transversale	524 mm ²
Nr. fire aluminiu	45
Nr. fire otel	7
Diametru fir aluminiu	3.85 mm
Diametru fir otel	2.57 mm
Diametru Conductor	30.78 mm
Greutate Aluminiu	1448.6 kg/km
Greutate Otel	283.6 kg/km
Greutate Conductor	1732.2 kg/km
Rezistenta Nominala	81.4 kN
Rezistenta Nominala HS	87.9 kN
Rezistenta Nominala EHS	95.2 kN
Rezistenta Nominala UHS	99.2 kN
Rezistenta CC @ 20°C	0.053 Ω/km
Capacitate Curent @ 85°C	797 A
Capacitate curent @ 150°C	1731 A
Capacitate Curent @ 210°C	1978 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.