


ACSS Conductor, 1042mm², Roadrunner



Specificații

Nume Conductor	Roadrunner/ACSS
Aria secțiunii transversale	1042 mm ²
Nr. fire aluminiu	76
Nr. fire oțel	19
Diametru fir aluminiu	4.18 mm
Diametru fir oțel	1.95 mm
Diametru Conductor	43.18 mm
Greutate Aluminiu	2897.3 kg/km
Greutate Oțel	444.1 kg/km
Greutate Conductor	3341.4 kg/km
Rezistența Nominală	142.4 kN
Rezistența Nominală HS	152.0 kN
Rezistența Nominală EHS	163.6 kN
Rezistența Nominală UHS	171.6 kN
Rezistența CC @ 20°C	0.027 Ω/km
Capacitate Curent @ 85°C	1188 A
Capacitate curent @ 150°C	2719 A
Capacitate Curent @ 210°C	3130 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.