


ACSS Conductor, 1274mm², Joree



Specificații

Nume Conductor	Joree/ACSS
Aria sectiunii transversale	1274 mm ²
Nr. fire aluminiu	76
Nr. fire otel	19
Diametru fir aluminiu	4.62 mm
Diametru fir otel	2.16 mm
Diametru Conductor	47.75 mm
Greutate Aluminiu	3542.4 kg/km
Greutate Otel	544.9 kg/km
Greutate Conductor	4087.3 kg/km
Rezistenta Nominala	174.3 kN
Rezistenta Nominala HS	186.2 kN
Rezistenta Nominala EHS	200.5 kN
Rezistenta Nominala UHS	210.2 kN
Rezistenta CC @ 20°C	0.022 Ω/km
Capacitate Curent @ 85°C	1321 A
Capacitate curent @ 150°C	3086 A
Capacitate Curent @ 210°C	3563 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.