


TACSR/AW Conductor, 67.35mm²



Specificații

Număr Fire Tal	6
Număr Fire Oțel	1
Diametru Fir Tal	3.50 mm
Diametru Fir Oțel	3.50 mm
Suprafață Secțională Fire Tal	57.73 mm ²
Suprafață Secțională Fire Oțel	9.62 mm ²
Suprafață Secțională Conductor	67.35 mm ²
Diametru Conductor	10.50 mm
Greutate Tal	158.42 kg/km
Greutate Oțel	63.39 kg/km
Greutate Conductor	221.81 kg/km
Rezistență Nominală HS	20.32 kN
Rezistență Nominală EHS	22.15 kN
Rezistență Nominală	N/A kN
Rezistență Nominală UHS	N/A kN
Rezistență DC @ 20°C	0.4956 Ω/km
Capacitate Curent @ 85°C	199 A
Capacitate Curent @ 150°C	328 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.