


TACSR/AW Conductor, 196.45mm²



Specificații

Număr Fire Tal	30
Număr Fire Oțel	7
Diametru Fir Tal	2.60 mm
Diametru Fir Oțel	2.60 mm
Suprafață Secțională Fire Tal	159.28 mm ²
Suprafață Secțională Fire Oțel	37.17 mm ²
Suprafață Secțională Conductor	196.45 mm ²
Diametru Conductor	18.20 mm
Greutate Tal	439.32 kg/km
Greutate Oțel	246.01 kg/km
Greutate Conductor	685.33 kg/km
Rezistență Nominală HS	71.52 kN
Rezistență Nominală EHS	77.47 kN
Rezistență Nominală	N/A kN
Rezistență Nominală UHS	N/A kN
Rezistență DC @ 20°C	0.1706 Ω/km
Capacitate Curent @ 85°C	408 A
Capacitate Curent @ 150°C	698 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.