


TACSR/AW Conductor, 379.56mm²



Specificații

Număr Fire Tal	26
Număr Fire Oțel	7
Diametru Fir Tal	4.00 mm
Diametru Fir Oțel	3.10 mm
Suprafață Secțională Fire Tal	326.73 mm ²
Suprafață Secțională Fire Oțel	52.83 mm ²
Suprafață Secțională Conductor	379.56 mm ²
Diametru Conductor	25.30 mm
Greutate Tal	902.23 kg/km
Greutate Oțel	349.64 kg/km
Greutate Conductor	1251.87 kg/km
Rezistență Nominală HS	115.35 kN
Rezistență Nominală EHS	122.21 kN
Rezistență Nominală	N/A kN
Rezistență Nominală UHS	N/A kN
Rezistență DC @ 20°C	0.0852 Ω/km
Capacitate Curent @ 85°C	617 A
Capacitate Curent @ 150°C	1085 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.