


TACSR/AW Conductor, 1260.75mm²



Specificații

Număr Fire Tal	84
Număr Fire Oțel	7
Diametru Fir Tal	4.20 mm
Diametru Fir Oțel	4.20 mm
Suprafață Secțională Fire Tal	1163.77 mm ²
Suprafață Secțională Fire Oțel	96.98 mm ²
Suprafață Secțională Conductor	1260.75 mm ²
Diametru Conductor	46.20 mm
Greutate Tal	3221.17 kg/km
Greutate Oțel	641.85 kg/km
Greutate Conductor	3863.0 kg/km
Rezistență Nominală HS	288.81 kN
Rezistență Nominală EHS	311.11 kN
Rezistență Nominală	N/A kN
Rezistență Nominală UHS	N/A kN
Rezistență DC @ 20°C	0.0246 Ω/km
Capacitate Curent @ 85°C	1256 A
Capacitate Curent @ 150°C	2369 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.