

ZTACSR Conductor, 586.9mm²



Specificații

Număr Fire Stal	54
Număr Fire Oțel	7
Diametru Fir Stal	3.5 mm
Diametru Fir Oțel	3.5 mm
Suprafață Secțională Fire Stal	519.5 mm ²
Suprafață Secțională Fire Oțel	67.4 mm ²
Suprafață Secțională Conductor	586.9 mm ²
Diametru Conductor	31.5 mm
Greutate Stal	1437.0 kg/km
Greutate Oțel	526.2 kg/km
Greutate Conductor	1963.3 kg/km
Rezistență Nominală HS	N/A kN
Rezistență Nominală EHS	N/A kN
Rezistență Nominală	167.7 kN
Rezistență Nominală UHS	186.2 kN
Rezistență DC @ 20°C	0.057 Ω/km
Capacitate Curent @ 85°C	778 A
Capacitate Curent @ 150°C	1398 A
Capacitate Curent @ 210°C	1745 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.