

ZTACSR Conductor, 629.8mm²



Specificații

Număr Fire Stal	54
Număr Fire Oțel	19
Diametru Fir Stal	3.6 mm
Diametru Fir Oțel	2.2 mm
Suprafață Secțională Fire Stal	558.9 mm ²
Suprafață Secțională Fire Oțel	70.9 mm ²
Suprafață Secțională Conductor	629.8 mm ²
Diametru Conductor	32.7 mm
Greutate Stal	1545.8 kg/km
Greutate Oțel	556.0 kg/km
Greutate Conductor	2101.8 kg/km
Rezistență Nominală HS	N/A kN
Rezistență Nominală EHS	N/A kN
Rezistență Nominală	183.4 kN
Rezistență Nominală UHS	202.6 kN
Rezistență DC @ 20°C	0.053 Ω/km
Capacitate Curent @ 85°C	812 A
Capacitate Curent @ 150°C	1465 A
Capacitate Curent @ 210°C	1831 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.