

ACSS/TW Conductor, 635.40mm², Oxbird



Specificații

Nume Conductor	Oxbird/ACSS/TW
Suprafață Secțională Fire Aluminiu	604.26 mm ²
Suprafață Secțională Fire Oțel	31.14 mm ²
Suprafață Secțională Conductor	635.40 mm ²
Nr. Fire Aluminiu	30
Nr. Fire Oțel	3
Diametru Fir Aluminiu	7 mm
Diametru Fir Oțel	2.38 mm
Diametru Conductor	29.64 mm
Greutate Aluminiu	1671.20 kg/km
Greutate Oțel	243.25 kg/km
Greutate Conductor	1914.45 kg/km
Rezistență Nominală	78.72 kN
Rezistență Nominală HS	84.32 kN
Rezistență Nominală EHS	kN
Rezistență Nominală UHS	93.97 kN
Rezistență DC @ 20°C	0.04590 Ω/km
Capacitate Curent @ 85°C	849 A
Capacitate Curent @ 200°C	1838 A
Capacitate Curent @ 250°C	2099 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.