

KTACSR/TW Conductor, 374.75mm²



Specificații

Suprafață Secțională Fire Ktal	170.45 mm ²
Suprafață Secțională Fire Oțel	9.46 mm ²
Suprafață Secțională Conductor	179.91 mm ²
Nr. Fire Ktal	14
Nr. Fire Straturi Ktal	2
Nr. Fire Oțel	1
Diametru Fir Oțel	3.47 mm
Diametru Conductor	15.60 mm
Greutate Ktal	469.95 kg/km
Greutate Oțel	73.57 kg/km
Greutate Conductor	543.52 kg/km
Rezistență Nominală	52.30 kN
Rezistență Nominală HS	53.62 kN
Rezistență Nominală EHS	54.57 kN
Rezistență Nominală UHS	54.90 kN
Rezistență DC @ 20°C	0.1876 Ω/km
Capacitate Curent @ 85°C	380 A
Capacitate Curent @ 150°C	648 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.