

KTACSR/TW Conductor, 818.19mm²



Specificații

Suprafață Secțională Fire Ktal	726.41 mm ²
Suprafață Secțională Fire Oțel	91.78 mm ²
Suprafață Secțională Conductor	818.19 mm ²
Nr. Fire Ktal	39
Nr. Fire Straturi Ktal	3
Nr. Fire Oțel	19
Diametru Fir Oțel	2.48 mm
Diametru Conductor	33.18 mm
Greutate Ktal	2012.6 kg/km
Greutate Oțel	719.55 kg/km
Greutate Conductor	2732.1 kg/km
Rezistență Nominală	273.65 kN
Rezistență Nominală HS	285.58 kN
Rezistență Nominală EHS	295.22 kN
Rezistență Nominală UHS	298.43 kN
Rezistență DC @ 20°C	0.044 Ω/km
Capacitate Curent @ 85°C	887 A
Capacitate Curent @ 150°C	1604 A

The above design is only a sample of the options available, for reference purposes only. Our policy of continuous improvement may result in a change of specifications without notice. If any discrepancies might be between the data sheet values and standards, we reserve the rights to make technical changes. Our company will not be held responsible, as all or any of pictures, drawings, weights and dimensions details or other elements in this document are only indicative and must not be considered contractual. Contact our sales team for other specifications or custom made products.